

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 Wax

Revision date: 03.01.2023

Product code: G0025

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

GYEON Q2 Wax

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Vehicle protective product - wax designed for paint.
Enthusiasts and professional use (End consumer)

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Gyeon Technology
Street: 1405-538, 212, Gasan digital 1-ro
Place: Geumcheon-gu, Seoul, Korea
Telephone: +82-10-4339-3599
Contact person: Robert Gyeon
e-mail: sales@gyeon.co

Supplier

Company name: Gyeon UK Ltd
Street: Commercial Quay, 84 Commercial Street
Place: GB-EH6 6LX Edinburgh
e-mail: hello@gyeonquartz.uk
Contact person: Richard Cooper Telephone: +44 (0)7984 056790

1.4. Emergency telephone number:

National Poisons Information Service - 03448920111. 'For healthcare professionals only'.

Further Information

Safety Data Sheet according to UK-REACH Regulation

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 3; H226
Asp. Tox. 1; H304
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Distillates (petroleum), hydro-treated light; Kerosine - unspecified

Signal word: Danger

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 Wax

Revision date: 03.01.2023

Product code: G0025

Page 2 of 12

H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

The substances in the mixture (> 0.1%) do not meet the PBT/vPvB criteria according to UK REACH. This product does not contain a substance (> 0,1%) that has endocrine disrupting properties with respect to humans as no components meets the criteria. This product does not contain a substance (> 0,1 %) that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria. In use, may form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (GB CLP Regulation)	
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified	45 - < 50 %
	265-149-8	649-422-00-2
	Flam. Liq. 3, Asp. Tox. 1; H226 H304	
153519-44-9	1,3-Benzenediol, 4-[4,6-Bis(2,4-Dimethylphenyl)-1,3,5-Triazin-2-Yl]-, Reaction Products With [(Dodecyloxy)Methyl]Oxirane And Oxirane Mono[(C10-16-Alkyloxy)Methyl] Derivatives	1 - < 3 %
	604-910-4	
	Aquatic Chronic 1; H410	
16961-83-4	fluorosilicic acid ... %	0.1 - < 0.2 %
	241-034-8	009-011-00-5
	Skin Corr. 1B; H314	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-47-8	265-149-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified	45 - < 50 %
		inhalation: LC50 = (> 5,3) mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

Further Information

- Distillates (petroleum), hydro-treated light; Kerosine - unspecified (P)
Note P: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0.1 % w/w benzene (Einecs No 200-753-7).

Product does not contain listed SVHC substances > 0.1 % according to UK REACH.

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 Wax

Revision date: 03.01.2023

Product code: G0025

Page 3 of 12

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth thoroughly with water. Let water be drunk in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation can cause damage to the respiratory tract or lungs.

May be fatal if swallowed and enters airways.

following inhalation: Headache. spasms. Repeated exposure may cause skin dryness or cracking. Caution if victim vomits: Risk of aspiration!

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Dry extinguishing powder. Alcohol resistant foam.

In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide (CO). Carbon dioxide (CO₂).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Ventilate affected area.

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Wear personal protection equipment (refer to section 8).

For emergency responders

No special measures are necessary.

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 Wax

Revision date: 03.01.2023

Product code: G0025

Page 4 of 12

6.2. Environmental precautions

- Do not allow to enter into surface water or drains.
- Eliminate leaks immediately.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- If required, notify relevant authorities according to all applicable regulations.

6.3. Methods and material for containment and cleaning up

For containment

- Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
- Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

- Clean contaminated objects and areas thoroughly observing environmental regulations.

Other information

- Ventilate affected area.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Provide adequate ventilation as well as local exhaust at critical locations.
- Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

- Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.
- Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

- The usual precautions for handling chemicals should be considered.
- Keep away from food, drink and animal feedingstuffs.
- Always close containers tightly after the removal of product. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing.

Further information on handling

- General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.
- Ensure adequate ventilation of the storage area.
- Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

- Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

- Keep the packing dry and well sealed to prevent contamination and absorption of humidity.
- Protect against: UV-radiation/sunlight. heat. Humidity frost.
- storage temperature: 15 - 25 °C

7.3. Specific end use(s)

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 Wax

Revision date: 03.01.2023

Product code: G0025

Page 5 of 12

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
16984-48-8	Fluoride (inorganic as F)	-	2.5		TWA (8 h)	WEL

8.2. Exposure controls



Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible). BS/EN 166

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves. (BS EN 374)

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time \geq 480 min. Penetration time (maximum wearing period): ~ 120 min. (estimated)

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of the Personal Protective Equipment at Work (Amendment) Regulations 2022 and the standard EN ISO 374.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Wear suitable protective clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

Exceeding exposure limit values

Insufficient ventilation

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 Wax

Revision date: 03.01.2023

Product code: G0025

Page 6 of 12

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid	
Colour:	light yellow	
Odour:	Squash	
Odour threshold:	not determined	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and boiling range:		82,3 °C
Flammability:		not determined
Lower explosion limits:		not determined
Upper explosion limits:		not determined
Flash point:		58 °C
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
pH-Value:		7
Viscosity / kinematic:		not determined
Water solubility:		not miscible
Solubility in other solvents		not determined
Dissolution rate:		not relevant
Partition coefficient n-octanol/water:		SECTION 12: Ecological information
Dispersion stability:		not relevant
Vapour pressure:		not determined
Density:		not determined
Bulk density:		not determined
Relative vapour density:		not determined
Particle characteristics:		not relevant

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
In use, may form flammable/explosive vapour-air mixture.	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	not relevant
Gas:	not relevant
Oxidizing properties	
none.	

Other safety characteristics

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	not determined
Solid content:	not determined
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
Viscosity / dynamic:	not determined
Flow time:	not determined

SECTION 10: Stability and reactivity

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 Wax

Revision date: 03.01.2023

Product code: G0025

Page 7 of 12

10.1. Reactivity

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.
Refer to chapter 10.5.

10.4. Conditions to avoid

Protect against: UV-radiation/sunlight. heat. Moisture.
In use may form flammable/explosive vapour-air mixture.
Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong. Strong acid. strong alkalis.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicokinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.
The product has not been tested.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 > 2000 mg/kg	Rabbit.	ECHA Dossier	
	inhalation (4 h) vapour	LC50 (> 5,3) mg/l	Rat	ECHA Dossier	

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.
Distillates (petroleum), hydro-treated light; Kerosine - unspecified:

In vitro mutagenicity/genotoxicity:

Method: OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells), OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test), OECD Guideline 471 (Bacterial Reverse Mutation Assay); Result: negative. Literature information: ECHA dossier

In vivo mutagenicity/genotoxicity:

Method: OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test), OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test); Result: negative. Literature information: ECHA dossier

Reproductive toxicity:

Method:-; Species: Sprague-Dawley Rat; Exposure route : oral; Result: NOAEL > 1500 mg/kg; Literature

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 Wax

Revision date: 03.01.2023

Product code: G0025

Page 8 of 12

information: ECHA dossier

Developmental toxicity/teratogenicity:

Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); Species: Sprague-Dawley Rat ;

Exposure route: oral; Result: NOAEL = 1000 mg/kg; Literature information: ECHA dossier

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Distillates (petroleum), hydro-treated light; Kerosine - unspecified:

Subchronic oral toxicity: Method:-; Species: Sprague-Dawley Rat ;Exposure duration: 90d; Result: NOAEL = 750 mg/kg ; Literature information: ECHA dossier; Subchronic inhalation toxicity: Method: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day); Species: Mouse; Exposure duration: 90d; Result: NOAEC = 1000 mg/kg; Literature information: ECHA dossier; Subchronic oral toxicity: Method: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study); Species: Sprague-Dawley Rat ; Exposure duration: 28d; Result: NOAEC = 0,5 ml/kg; Literature information: ECHA dossier

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance (> 0,1%) that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Further information

Solvent:

Symptoms: Depression of the central nervous system. Liver and kidney damage. drowsiness. vomiting.

Nausea. Dizziness. unconsciousness. Impaired consciousness. Intoxication. erythema (redness)

SECTION 12: Ecological information

12.1. Toxicity

The product has not been tested.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified					
	Acute algae toxicity	ErC50 3 mg/l	EL50: 1-	72 h	Pseudokirchneriella subcapitata	ECHA Dossier
	Acute crustacea toxicity	EC50 1,4 mg/l	EL50:	48 h	Daphnia magna	ECHA Dossier

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-47-8	Distillates (petroleum), hydro-treated light; Kerosine - unspecified			
	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D	61	28	ECHA Dossier

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

No data available.

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 Wax

Revision date: 03.01.2023

Product code: G0025

Page 9 of 12

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.
The aforementioned statement applies to substances contained in the product with a minimum content of 0.1 %.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.
The aforementioned statement applies to substances contained in the product with a minimum content of 0.1 %.

12.7. Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.
Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - used product

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	UN 1993
<u>14.2. UN proper shipping name:</u>	FLAMMABLE LIQUID, N.O.S. (Distillates (petroleum), hydro-treated light; Kerosine - unspecified)
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	III
Hazard label:	3



Classification code: F1

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 Wax

Revision date: 03.01.2023

Product code: G0025

Page 10 of 12

Special Provisions: 274 601
 Limited quantity: 5 L
 Excepted quantity: E1
 Transport category: 3
 Hazard No: 30
 Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Distillates (petroleum), hydro-treated light; Kerosine - unspecified)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Classification code: F1
 Special Provisions: 274 601
 Limited quantity: 5 L
 Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Distillates (petroleum), hydro-treated light; Kerosine - unspecified)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Marine pollutant: NO
 Special Provisions: 223, 274, 955
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Distillates (petroleum), hydro-treated light; Kerosine - unspecified)
14.3. Transport hazard class(es): 3
14.4. Packing group: III
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 10 L
 Passenger LQ: Y344
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 355
 IATA-max. quantity - Passenger: 60 L
 IATA-packing instructions - Cargo: 366

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 Wax

Revision date: 03.01.2023

Product code: G0025

Page 11 of 12

IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

See section 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): not determined

2004/42/EC (VOC): not determined

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Additional information

Safety Data Sheet according to UK-REACH Regulation

The mixture is classified as hazardous according to GHS (GB CLP).

UK REACH Appendix XVII, No (mixture): 3, 40

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Rev. 1.00; Initial release: 13.11.2020

Rev. 1.10; 02.02.2021, Changes in chapter: 2,9,16.

Rev. 1.11; 17.03.2021, Changes in chapter: 1,16.

Rev. 1.12; 09.04.2021, Changes in chapter: 3.

Rev. 2.00; 03.01.2023, Changes in chapter: 1,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

ECHA: European Chemicals Agency

EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

Safety Data Sheet

according to UK REACH Regulation

GYEON Q2 Wax

Revision date: 03.01.2023

Product code: G0025

Page 12 of 12

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organization
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
 h: hour
 LOAEL: Lowest observed adverse effect level
 LOAEC: Lowest observed adverse effect concentration
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NOAEL: No observed adverse effect level
 NOAEC: No observed adverse effect concentration
 NLP: No-Longer Polymers
 N/A: not applicable
 OECD: Organisation for Economic Co-operation and Development
 PNEC: predicted no effect concentration
 PBT: Persistent bioaccumulative toxic
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 REACH: Registration, Evaluation, Authorisation of Chemicals
 SVHC: substance of very high concern
 TRGS: Technische Regeln für Gefahrstoffe
 UN: United Nations
 VOC: Volatile Organic Compounds

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)